





105897 / 97443 / 106665 / 93632



106664 / 97451



105789

Our stainless steel range features an electrolytical polishing surface treatment. Using this process improves noticeably the resistance to marine corrosion and contributes to a long-lasting shiny stainless steel surface.

Depending on the references, the head of the stanchion may be spherical or cylindrical. These stanchions, manufactured with a 316 stainless steel, are available with or without drilling for toe rail mounting.

They comply with ISO 15085 standard.



Stanchion base

All models with welded nut fit on the base 115633.

Code	Model	Guardrails	A (mm)	B (mm)	C (mm)	D (mm)	Spacing (mm)	Diameter (mm)	End
97443	Stanchion	1	450	-	35	-	-	25	Cylindrical
106665*	Stanchion	2	630	330	-	45	-	25	Cylindrical
93632	Stanchion	2	630	330	35	45	-	25	Cylindrical
105897	Stanchion	2	610	310	35	18	-	25	Spherical
106664*	Gate stanchion	2	630	330	-	45	280	25	-
97451	Gate stanchion	2	630	300	35	45	280	25	-
105789	Gate door	2	615	330	-	18	280	25	-
115633	Base	-	-	-	-	-	-	60	-

* with welded nut

"C" refers to in-line drilling and "D" to across drilling.

