



# The First 36.7

## Standard Equipment and Options



LOA	.....	36'0"
Hull Length	.....	35'0"
LWL	.....	30'3"
Beam	.....	11'4"
Displacement	.....	12,939 lbs (approx)
Sail Area	.....	100% foretriangle . . . 666 sq ft
Draft	.....	(standard) 5'11" . . . (optional) 7'3"
Ballast (standard)	.....	3,993 lbs
Ballast (optional)	.....	3,549 lbs
Fuel Capacity	.....	.20 gal
Water	.....	.72 gal
Auxiliary	.....	.29 hp
Construction:	Marion, South Carolina, USA	
Hull Design:	Farr Yacht Design	

Rig Dimensions: Mast	.....	Classic
I	.....	46'5"
J	.....	13'0"
P	.....	45'5"
E	.....	15'7"

### CONSTRUCTION

Hull constructed of hand-laid solid GRP bonded to a structural grid/hull liner of directional fiberglass/GRP for a strong, stiff, light composite. Vinylester hull barrier coat to resist osmotic blistering and zone-specific stitchmat laminates for specific increased strength optimization.

Deck constructed of Cored GRP sandwich construction for stiffness, thermal and acoustic insulation and lighter weight. Solid fiberglass reinforcements in high load areas. Integral unidirectional GRP deck beams for added strength. Main bulkheads bonded 360° to the hull and deck for rigid torsional and compression strength.

### ON DECK

Stainless steel stemhead fitting with roller  
Self-bailing anchor locker with cleat  
Stainless steel bow pulpit with navigation lights  
Solid wood toe rail along the hull-deck junction  
(4) Aluminum mooring cleats  
SS stanchions, bases and double lifelines  
(1) Lewmar® racing mainsheet traveller track with ball-bearing car, adjustable under tension  
(2) Lewmar® racing genoa sheet tracks adjustable under tension  
Mainsheet tackle with ball-bearing blocks, and fine tune adjustment.  
(2) Lewmar® 40 AST maneuvering winches  
(2) Lewmar® 48 AST genoa sheet winches  
Spinlock® XT deckstoppers  
Wichard® foldaway padeyes for spinnaker blocks  
(2) Semi-recessed shroud chainplates  
Edson® "CDI" wheel steering with compass  
51" Diameter Edson steering wheel  
Self-aligning upper and lower rudder bearings  
(2) Lazzaretto cockpit lockers  
Solid wood helmsman seat  
Solid wood-slatted cockpit seats  
(2) Removable cockpit seat lockers  
Aft lockers: port for gas bottle, starboard for storage  
Liferaft compartment below helm seat  
Emergency tiller  
Stainless steel aft pulpit with aft pulpit opening  
lifelines and horseshoe buoy holder  
Stern light on pulpit  
Stainless steel swim ladder  
Cold cockpit shower

### STANDING RIGGING

9/10 fractional rig  
Double spreaders  
Anodized aluminum boom  
Mast step fitting with Lewmar® blocks  
Stainless standing rigging  
Navtec® rod  
Backstay adjuster  
Sparcraft® rigid boom vang  
Tuff Luff® headstay foil

### RUNNING RIGGING

(1) Mainsail halyard  
(1) Genoa halyard  
Double-ended mainsheet  
(2) Genoa sheets  
(2) Reefing lines  
(1) Outhaul line, vang line  
Bridle backstay adjuster

### SAILS

Optional racing or cruising sails available

### FORWARD CABIN

Double v-berth (6'5" x 5'2")  
Storage under berth  
Shelves alongside hull  
Hanging locker  
Opening Lewmar® deck hatch  
Halogen reading lights

### HEAD

Fully molded head compartment w/USCG approved marine toilet and holding tank - 10 gallon  
Round wash basin with mixer tap, pressurized hot and cold shower  
Mirror  
Towel hook and accessories  
Overhead light  
Lewmar® opening hatch

### SALON

Settee with cushions and back rests  
Removable salon table with folding leaves and stainless steel pedestal base  
Lockers above the seat-backs  
Storage in the settee back rests  
Lewmar® opening hatch with blind  
Fixed hull ports  
Grabrails  
Overhead halogen lights  
Opening ports  
Pressure laminate floorboard

### GALLEY

Double stainless steel rectangular sinks w/mixer tap  
pressurized hot and cold water  
Gimbale 2-burner LPG stove with oven and storage underneath  
12 Volt electric refrigeration  
Cutlery drawer  
Trash can  
Storage compartments with doors  
Overhead lights  
(1) Lewmar® opening port  
Wooden hand rail  
Halogen lights

### NAV STATION

Chart table with storage  
Space for instruments  
Storage for charts  
Storage under nav seat  
12 Volt electrical panel  
Wooden hand rail  
Lewmar® opening port

### AFT CABINS

One to port: "queen" double berth (6'6" x 5'8")  
One to starboard: oversized single berth (6'6" x 3'8")  
Hanging locker  
Shelves along the hull  
Storage space under berth  
Reading light  
(1) Lewmar® port opening into the cockpit  
(1) Lewmar® port opening into the cabin side

### PLUMBING

Electric bilge pump  
Hand-operated bilge pump  
72 gals fresh water capacity  
Pressurized water system  
12 Volt shower drain pump

### ELECTRICAL

12 Volt circuit  
(2) 80 Amp batteries  
14-functions electrical panel  
Navigation lights  
110 Volt shore power w/cable  
110 Volt battery charger (20 Amp)

### ENGINE EQUIPMENT

20 gallon fuel tank  
Engine compartment soundproofed and insulated to CE standards.  
Volvo® 29 hp DI-30 saildrive - fresh water cooled  
Two-blade folding propeller  
Hour meter and fuel gauge

### MISCELLANEOUS

(2) Winch handles  
Owner's handbook  
AM-FM stereo with single CD player and speakers

### OPTIONS

Consult your dealer for all available options