

SPINNAKER POLES & BOWSPRITS



>> From Spinnaker to Gennaker/Code zero :

From small boats to maxi-yachts, cruising or racing, Sparcraft supplies the best equipment perfectly adapted to your sailing program (asymmetric/symmetric Spinnaker, Gennaker & Code zero). This chapter contains the new tapered pre-impregnated carbon spi poles and the new range of bowsprits.

RELIABILITY

LIGHTNESS

RESISTANCE

Aluminium spi poles	P50
Carbon spi poles	P51 & P52
Bowsprits	P53
Code 0 and Gennaker furlers	P54

Photo : © Grand Soleil



SPINNAKER & GENNAKER EQUIPMENT

ALUMINIUM & CARBON SPI POLES

ALUMINIUM SPINNAKER POLES

Reliability & resistance



Sparcraft poles have been proven over millions of miles thanks to simple pole ends and high quality tubes. In this way, Sparcraft makes your Spinnaker handling easier. The spi poles have been designed to protect the crew and the equipment while making the spi handling easier.

TANGONS ALUMINIUM

- Two types: symetric and asymetrics spinnaker poles (see datas below);
- Standard & automatic pole ends with anodized fitting & stainless steel mechanism;



- Anodized tube 6005A T6. Manufactured with high quality aluminium alloy from european origin;
- Automatic pole ends: remote opening:

TYPE 1



TYPE 2



OPTION



- Composite or aluminium ends:
 - Trigger piston end ø 47 (simple);
 - Automatic trigger piston end ø 47;
 - Automatic trigger piston end ø 71;
 - Automatic trigger piston end ø 89;

Type of assembly	ø Tube (mm)	Max length section (mm)	Inboard end	Outboard end
SYMMETRIC SPI POLE				
Type 1	40	3000	Pist ø 36	Pist ø 36
Type 1	55	3350	Pist ø 55	Pist ø 55
Type 1	63	4000	Pist ø 55	Pist ø 55
Type 1	80	5300	Pist ø 55	Pist ø 55
ASYMMETRIC SPI POLE				
Type 2 (Track 32x5)	80	5300	Male fitting for bel	Pist ø 55
Type 2 (integrated to the mast)	80	5300	Male fitting for bel	Pist ø 55
Type 2 (Track 32x5)	90	4500	ditto	Pist ø 55
Type 2 (Track 32x5)	100	6000	ditto	Pist ø 80
Type 2 (integrated to the mast)	100	6000	ditto	Pist ø 80
Type 2 (Track 32x5)	125	7000	ditto	Pist ø 80
Type 2 (ouhaul cars F40)	125	7000	ditto	Pist ø 80

Automatic or not
Option : Vectran briddles

RINGS & ACCESSORIES



Photo credit : Yves Ronzier / RIM 1350 RIM-Yachts

Reduction rings :

- The reduction rings offer the possibility to change ends while keeping the existing tubes.

Delrin Spi pole ring	
sup ø x inf ø	ø 63 x ø 58
	ø 80 x ø 70
	ø 100 x ø 70
	ø 125 x ø 70

Other accessories:

- Mast stowage systems, tracks, spi, eyes, pole stowage: see mast chapter p. 26